SAFETY DATA SHEET

Issuing Date No data available

Revision Date 28-Aug-2014

Revision Number 1



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name Cover All Liquid #646

Other means of identification

UN-No. UN1268

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Rubber and Vinyl Protectant - Non-aerosol

Uses advised against No information available

Details of the supplier of the safety data sheet

Distributed by: 1st Ayd Corporation

1325 Gateway Drive Elgin, IL 60124 Phone: 847-622-0001

Emergency Response Number: 800-255-3924

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Germ cell mutagenicity	Category 1B
Reproductive toxicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1



Cover All Liquid #646 Revision Date 28-Aug-2014

Flammable liquids Category 2

GHS Label elements, including precautionary statements

Emergency Overview

Signal word

Danger

Hazard Statements

Causes skin irritation

May cause genetic defects

Suspected of damaging fertility or the unborn child

May cause damage to organs through prolonged or repeated exposure

May be fatal if swallowed and enters airways

Highly flammable liquid and vapor



Appearance Clear Blue

Physical State Liquid

Odor Unique

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Do not breathe dust/fume/gas/mist/vapors/spray

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ ventilating/ lighting/ equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Specific treatment (see supplemental first aid instructions on this label)

Skin

If skin irritation occurs: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep cool



Cover All Liquid #646 Revision Date 28-Aug-2014

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity

Other information

May be harmful in contact with skin Harmful to aquatic life with long lasting effects PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION

Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%	Trade Secret
Solvent naphtha (petroleum), light aliphatic	64742-89-8	30 - 60	*
Hexane	110-54-3	10 - 30	••
Diethyl Phthalate (DEP)	84-66-2	0.1 - 1	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures

General Advice Call 911 or emergency medical service. Remove and isolate contaminated

clothing and shoes.

Eye Contact Call a physician immediately.

Skin Contact Wash skin with soap and water.

Inhalation Move victim to fresh air. Give artificial respiration if victim is not breathing.

Administer oxygen if breathing is difficult.

Ingestion Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water.

> Never give anything by mouth to an unconscious person. Aspiration hazard if swallowed - can enter lungs and cause damage. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Call a physician or poison control

center immediately.

Self-protection of the first aider Ensure that medical personnel are aware of the material(s) involved, take

precautions to protect themselves and prevent spread of contamination.

Most important symptoms and effects, both acute and delayed

Cover All Liquid #646

Most Important Symptoms and Difficulty in breathing. Coughing and/ or wheezing. Dizziness. **Effects**

Indication of any immediate medical attention and special treatment needed

Notes to Physician

Keep victim warm and quiet.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical, CO2, water spray or regular foam. Water spray, fog or regular foam. Use water spray or fog; do not use straight streams.

Unsuitable Extinguishing Media

CAUTION: All these products have a very low flash point. Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical

Vapors can form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard. Substance may be transported hot.

Uniform Fire Code

Flammable Liquid: I-B

Hazardous Combustion Products

Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact

No.

Sensitivity to Static Discharge

Yes.

Protective equipment and precautions for firefighters

Move containers from fire area if you can do it without risk.

Cover All Liquid #646 Revision Date 28-Aug-2014

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

All equipment used when handling the product must be grounded. Do not touch or walk

through spilled material. Stop leak if you can do it without risk.

Other Information Water spray may reduce vapor; but may not prevent ignition in closed spaces.

Environmental Precautions

Environmental Precautions Prevent entry into waterways, sewers, basements or confined areas.

Methods and material for containment and cleaning up

Methods for Containment A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth,

sand or other non-combustible material and transfer to containers.

Methods for cleaning up Use clean non-sparking tools to collect absorbed material. Dike far ahead of liquid spill for

later disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with

skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to

package label instructions.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up.

Protect from moisture. Keep out of the reach of children. Store away from other materials. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with

the particular national regulations. Store in accordance with local regulations.

Incompatible Products Strong acids. Strong oxidizing agents. Strong bases.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH



Hexane 110-54-3	TWA: 50 ppm S*	TWA: 500 ppm TWA: 1800 mg/m³ (vacated) TWA: 50 ppm (vacated) TWA: 180 mg/m³	IDLH: 1100 ppm Ceiling: 510 ppm 15 min Ceiling: 1800 mg/m³ 15 min TWA: 50 ppm TWA: 180 mg/m³
Diethyl Phthalate (DEP) 84-66-2	TWA: 5 mg/m ³	(vacated) TWA: 5 mg/m ³	

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

Appropriate engineering controls

Engineering Measures

Showers

Liquid

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection

Tight sealing safety goggles.

Skin and Body Protection

Wear protective gloves and protective clothing. Long sleeved clothing. Impervious gloves.

Chemical resistant apron. Antistatic boots.

Respiratory Protection

No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures

Physical State

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

i ilyalcai otate	Liquid		
Appearance	Clear Blue	Odor	Unique
Color	No information available	Odor Threshold	No information available
Durant			
Property	<u>Values</u>	Remarks/ Method	
pH	7	None known	
Melting / freezing point	No data available	None known	
Boiling point / boiling range	No data available	None known	
Flash Point	22 C / 72 F	None known	
Evaporation Rate	No data available	None known	
Flammability (solid, gas)	No data available	None known	
Flammability Limit in Air			
Upper flammability limit	No data available		
Lower flammability limit	No data available		
Vapor pressure	No data available	None known	
Vapor density	No data available	None known	
Specific Gravity	No data available	None known	
Water Solubility	Insoluble in water	None known	
Solubility in other solvents	No data available	None known	



Cover All Liquid #646 Revision Date 28-Aug-2014

Partition coefficient: n-octanol/waterNo data availableNone knownAutoignition temperatureNo data availableNone knownDecomposition temperatureNo data availableNone knownKinematic viscosityNo data availableNone knownDynamic viscosityNo data availableNone known

Explosive properties No data available Oxidizing Properties No data available

Other Information

Softening Point
VOC Content (%)
Particle Size
No data available
No data available
No data available

Particle Size Distribution

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong acids. Strong oxidizing agents. Strong bases.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information Product does not present an acute toxicity hazard based on known or supplied information.

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of

respiratory tract. Aspiration into lungs can produce severe lung damage. May cause

pulmonary edema. Pulmonary edema can be fatal.

Eye Contact Specific test data for the substance or mixture is not available. Expected to be an irritant

based on components. Irritating to eyes. May cause redness, itching, and pain. May cause

irritation.

Skin Contact Specific test data for the substance or mixture is not available. Expected to be an irritant

based on components. Irritating to skin. Repeated exposure may cause skin dryness or

cracking.



Revision Date 28-Aug-2014

Ingestion

Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Solvent naphtha (petroleum), light aliphatic 64742-89-8	-	= 3000 mg/kg(Rabbit)	-
Hexane 110-54-3	= 15000 mg/kg (Rat)	= 3000 mg/kg(Rabbit)	= 48000 ppm (Rat) 4 h
Diethyl Phthalate (DEP) 84-66-2	-	> 11200 mg/kg(Rat)	-

Information on toxicological effects

Symptoms

Erythema (skin redness). May cause redness and tearing of the eyes. Difficulty in breathing. Coughing and/ or wheezing. Asthma-like and/ or skin allergy-like symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization

No information available.

Mutagenic Effects

There is no data available for this product. Contains a known or suspected mutagen.

Carcinogenicity

Contains no ingredient listed as a carcinogen.

Reproductive Toxicity

Contains a known or suspected reproductive toxin.

STOT - single exposure

No information available.

STOT - repeated exposure

Causes damage to organs through prolonged or repeated exposure. Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from chronic or repeated exposure. (STOT RE).

Chronic Toxicity

No known effect based on information supplied. Contains a known or suspected mutagen. Possible risk of irreversible effects. Contains a known or suspected reproductive toxin. Aspiration may cause pulmonary edema and pneumonitis. Avoid repeated exposure.

Prolonged exposure may cause chronic effects.

Target Organ Effects

Respiratory system. Eyes, Skin. May affect the genetic material in germ cells (sperm and eggs). Reproductive System. Central Nervous System (CNS). Peripheral Nervous System

(PNS).

Aspiration Hazard

No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 84,270.00 mg/kg



ATEmix (dermal) 4,213.00 mg/kg (ATE) ATEmix (inhalation-vapor) 948.44 ATEmix

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects.

Persistence and Degradability

No information available.

Bioaccumulation

Chemical Name	Log Pow
Diethyl Phthalate (DEP)	2.35
84-66-2	

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods

This material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261).

Contaminated Packaging

Dispose of contents/containers in accordance with local regulations.

US EPA Waste Number

D001

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Diethyl Phthalate (DEP)	U088	Included in waste stream:		U088
84-66-2		F039		

California Hazardous Waste Codes 331

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Hexane	Toxic
110-54-3	Ignitable

14. TRANSPORT INFORMATION

DOT

UN-No.

UN1268

Proper Shipping Name

PETROLEUM DISTILLATES, N.O.S.

Hazard Class
Packing Group

3

Description

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, II



Emergency Response Guide 128 Number TDG UN-No. UN1268 **Proper Shipping Name** PETROLEUM DISTILLATES, N.O.S. **Hazard Class** Packing Group Ш Description UN1268, PETROLEUM DISTILLATES, N.O.S., 3, II MEX UN-No. UN1268 **Proper Shipping Name** PETROLEUM DISTILLATES, N.O.S. Hazard Class 3 Packing Group Ш Description UN1268, PETROLEUM DISTILLATES, N.O.S., 3, II I<u>CAO</u> UN-No. UN1268 **Proper Shipping Name** PETROLEUM DISTILLATES, N.O.S. **Hazard Class Packing Group** Ш Description UN1268, PETROLEUM DISTILLATES, N.O.S., 3, II IATA UN1268 UN-No. **Proper Shipping Name** PETROLEUM DISTILLATES, N.O.S. **Hazard Class Packing Group** \parallel Description UN1268, PETROLEUM DISTILLATES, N.O.S., 3, II IMDG/IMO UN-No. UN1268 **Proper Shipping Name** PETROLEUM DISTILLATES, N.O.S. **Hazard Class** 3 **Packing Group** 11 EmS No. F-E, S-E Description UN1268, PETROLEUM DISTILLATES, N.O.S., 3, II, (22°C C.C.) RID UN-No. UN1268 PETROLEUM DISTILLATES, N.O.S. **Proper Shipping Name Hazard Class** 3 **Packing Group** П Classification code Description UN1268, PETROLEUM DISTILLATES, N.O.S., 3, II <u>ADR</u> UN-No. UN1268 **Proper Shipping Name** PETROLEUM DISTILLATES, N.O.S. **Hazard Class Packing Group** 11 Classification code F1 Tunnel restriction code Description UN1268, PETROLEUM DISTILLATES, N.O.S., 3, II ADN UN-No. UN1268 **Proper Shipping Name** PETROLEUM DISTILLATES, N.O.S.



Hazard Class

Packing Group Classification code

II F1

Special Provisions

363, 640C

Description

UN1268, PETROLEUM DISTILLATES, N.O.S., 3, II

Limited Quantity Ventilation 1 L VE01

15. REGULATORY INFORMATION

International Inventories

TSCA

Complies

DSL IECSC All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No.	Weight-%	SARA 313 - Threshold Values %
Hexane - 110-54-3	110-54-3	10 - 30	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Diethyl Phthalate (DEP) 84-66-2		X	Х	

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Hexane 110-54-3	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Diethyl Phthalate (DEP) 84-66-2	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations



Revision Date 28-Aug-2014

Cover All Liquid #646

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Hexane 110-54-3	Х	Х	Х	Х	X
Diethyl Phthalate (DEP) 84-66-2	X	Х	Х	Х	

International Regulations

Mexico

National occupational exposure limits

Component	Carcinogen Status	Exposure Limits
Hexane		Mexico: TWA 50 ppm
110-54-3 (10 - 30)		Mexico: TWA 176 mg/m ³
·		Mexico: STEL 1000 ppm
		Mexico: STEL 3500 mg/m ³
Diethyl Phthalate (DEP)		Mexico: TWA 5 mg/m ³
84-66-2 (0.1 - 1)		Mexico: STEL 10 mg/m³

Mexico - Occupational Exposure Limits - Carcinogens

Canada WHMIS Hazard Class B2 - Flammable liquid





16. OTHER INFORMATION

NFPA Health Hazards 1 Flammability 3 Instability 0 Physical and Chemical Hazards - HMIS Health Hazards 2 * Flammability 3 Physical Hazard 0 Personal Protection

Chronic Hazard Star Legend * = Chronic Health Hazard

Prepared By Product Stewardship

23 British American Blvd. Latham, NY 12110

1-800-572-6501 28-Aug-2014

Revision Note No information available

Disclaimer

Revision Date

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet



Χ