Version 4.0	Revision Date 04/19/2018	Print Date 10/16/2019
SECTION 1. PRODUCT AND		

Material name : A00142 MST PAINLESS STAINLESS 20NET18

Material number	:	00000000001001557
Manufacturer or supplier's o	leta	nils
Company	:	1st Ayd Corporation
Address	:	1325 Gateway Drive Elgin, IL 60124
Telephone	:	847-622-0001

Emergency telephone nu	nbers
For a Medical Emergency	: 800-255-3924

Recommended use of the chemical and restrictions on use

Recommended use : Cleaner

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Aerosol containing a liquefied gas
Colour	light cream
Odour	characteristic

GHS Classification

Gases under pressure Skin sensitisation		Liquefied gas Category 1
GHS label elements		
Hazard pictograms	:	
Signal word	:	Warning
Hazard statements	:	H280 Contains gas under pressure; may explode if heated. H317 May cause an allergic skin reaction.
Precautionary statements	:	Prevention: P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves. P251 Pressurized container: Do not pierce or burn, even after

Version 4.0	Revision Date 04/19/2018	Print Date 10/16/2019
	use. Response: P302 + P352 IF ON SKIN: Wash P333 + P313 If skin irritation or ra advice/ attention. P363 Wash contaminated clothin Storage: P410 + P403 Protect from sunligh place. P412 Do not expose to temperatu Disposal: P501 Dispose of contents/contair regulation.	ash occurs: Get medical g before reuse. nt. Store in a well-ventilated ures exceeding 50 °C/ 122 °F.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
Distillates (petroleum), hydrotreated light	64742-47-8	>= 10 - < 20
propane	74-98-6	>= 5 - < 10
butane	106-97-8	>= 3 - < 5
Naphtha (petroleum), hydrotreated light	64742-49-0	>= 1 - < 3
Solvent naphtha (petroleum), heavy aliph.	64742-96-7	>= 1 - < 3
citral	5392-40-5	>= 0.1 - < 1

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

General advice	 Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	 If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	 If skin irritation persists, call a physician. Wash off with soap and water. Wash off immediately with plenty of water for at least 15 minutes. If on clothes, remove clothes. Wash contaminated clothing before re-use.
In case of eye contact	 Rinse immediately with plenty of water for at least 15 minutes. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.

Version 4.0	F	Revision Date 04/19/2018	Print Date 10/16/2019
If swallowed	D p N	eep respiratory tract clear. O NOT induce vomiting unless directe hysician or poison control center. lever give anything by mouth to an und symptoms persist, call a physician.	
Most important symptoms and effects, both acute and delayed	S M	ffects are immediate and delayed. Symptoms may include irritation, redner May cause an allergic skin reaction. Review section 2 of SDS to see all pote	
Notes to physician	: Т	reat symptomatically. Symptoms may	v be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical Water spray jet
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during firefighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products Specific extinguishing methods		Carbon dioxide (CO2) Carbon monoxide Smoke Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions,	 Use personal protective equipment.
protective equipment and	Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive
emergency procedures	concentrations. Vapours can accumulate in low areas. Ensure adequate ventilation. Remove all sources of ignition.
Environmental precautions	 Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform

Version 4.0	Revision Date 04/19/2018	Print Date 10/16/2019
	respective authorities.	
Methods and materials for containment and cleaning up	: Soak up with inert absorbent mate acid binder, universal binder, saw Keep in suitable, closed container	dust).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	:	 Provide sufficient air exchange and/or exhaust in work rooms. Do not breathe vapours or spray mist. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations. Always replace cap after use.
Conditions for safe storage	:	BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. No smoking. Keep in a dry, cool and well-ventilated place. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
Materials to avoid	:	Oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated light	64742-47-8	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
		PEL (particulate)	5 mg/m3	CAL PEL
propane	74-98-6	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm	OSHA Z-1

A00142 MST PAINLESS STAINLESS 20NET18

ersion 4.0	Revision I	Date 04/19/2018	Print I	Date 10/16/2019
		1	1,800 mg/m3	
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0
		PEL	1,000 ppm 1,800 mg/m3	CAL PEL
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm 1,900 mg/m3	OSHA P0
		PEL	800 ppm 1,900 mg/m3	CAL PEL
citral	5392-40-5	TWA (Inhalable fraction and vapor)	5 ppm	ACGIH
Personal protective equip Respiratory protection	: Use respir ventilation	is provided or ex	unless adequate loc posure assessmen ecommended expos	t demonstrates
Hand protection Material Remarks		 Protective gloves The suitability for a specific workplace should be discussed with the producers of the protective gloves. 		
	with the pr			be discussed
Eye protection	: Safety glas Ensure tha	oducers of the posses		
Eye protection Skin and body protection	Safety glas Ensure tha the workst Impervious Choose bo	roducers of the p sses at eyewash static ation location. s clothing ody protection ac	rotective gloves.	vers are close to unt and
	 Safety glas Ensure tha the workst Impervious Choose bo concentrat When usin When usin 	roducers of the p sses at eyewash static ation location. s clothing ody protection ac tion of the dange ng do not eat or d ng do not smoke.	rotective gloves. Ins and safety show cording to the amou rous substance at th	vers are close to unt and ne work place.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Aerosol containing a liquefied gas
Colour	:	light cream
Odour	:	characteristic
Odour Threshold	:	No data available
рН	:	No data available

rsion 4.0	Revision Date 04/19/2018	Print Date 10/16/2019
Melting point/freezing point	: No data available	
Boiling point	: No data available	
Flash point	: No data available	
Evaporation rate	: No data available	
Flammability (solid, gas)	: The product is not flammable.	
Upper explosion limit	: No data available	
Lower explosion limit	: No data available	
Vapour pressure	: No data available	
Relative vapour density	: No data available	
Density	: 0.938 g/cm3	
Solubility(ies)		
Water solubility	: partly soluble	
Solubility in other solvents	: not determined	
Partition coefficient: n- octanol/water	: No data available	
Auto-ignition temperature	: not determined	
Thermal decomposition	: No data available	
Viscosity		
Viscosity, kinematic	: No data available	
Heat of combustion	: 15.00 kJ/g	

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Version 4.0	Revision Date 04/19/2018	Print Date 10/16/2019
Potential Health Effects		
Aggravated Medical Condition	: None known.	
Symptoms of Overexposure	: Effects are immediate and delayed Symptoms may include irritation, re	
Carcinogenicity:		
IARC	No component of this product present equal to 0.1% is identified as probable human carcinogen by IARC.	
ACGIH	No component of this product present equal to 0.1% is identified as a carcin carcinogen by ACGIH.	
OSHA	No component of this product present equal to 0.1% is on OSHA's list of reg	
NTP	No component of this product present equal to 0.1% is identified as a knowr by NTP.	at levels greater than or
Acute toxicity		
Product:		
Acute oral toxicity	: Acute toxicity estimate : > 5,000 m Method: Calculation method	g/kg
Acute dermal toxicity	: Acute toxicity estimate : > 5,000 m Method: Calculation method	g/kg
Components:		
Distillates (petroleum), hyd Acute oral toxicity	rotreated light: : LD50 Rat: > 5,000 mg/kg	
Acute inhalation toxicity	: LC50 Rat: > 4.6 mg/l Exposure time: 6 h	
Acute dermal toxicity	: LD50 Rat: > 2,000 mg/kg	
Skin corrosion/irritation		
Product:		
Remarks: May cause skin irrit	tation and/or dermatitis.	
Serious eye damage/eye irritatio	on	
Product:		
Remarks: May irritate eyes.		

Respiratory or skin sensitisation

A00142 MST PAINLESS STAINLESS 20NET18

Version 4.0	Revision Date 04/19/2018	Print Date 10/16/2019
Product:		

Remarks: Causes sensitisation.

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: No data available

<u>Components:</u> Distillates (petroleum), hydrotreated light: Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available **Bioaccumulative potential**

Product:

Partition coefficient: n- octanol/water <u>Components:</u>	:	Remarks: No data available
butane : Partition coefficient: n- octanol/water citral :	:	Pow: 2.89

A00142 MST PAINLESS STAINLESS 20NET18	

Version 4.0	Revision Date 04/19/2018	Print Date 10/16/2019
Partition coefficient: n- octanol/water	: Pow: 2.76	
Mobility in soil		
No data available		
Other adverse effects		
No data available <u>Product:</u>		
Regulation Remarks	40 CFR Protection of Environment Stratospheric Ozone - CAA Section Substances This product neither contains, nor with a Class I or Class II ODS as d Clean Air Act Section 602 (40 CFR + B).	n 602 Class I was manufactured lefined by the U.S.
Additional ecological information	: An environmental hazard cannot b event of unprofessional handling o aquatic life with long lasting effects	r disposal., Harmful to
<u>Components:</u> Distillates (petroleum), hydro	treated light :	
Additional ecological information	: No data available	

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of in accordance with local regulations.
Contaminated packaging	 Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: IATA (Cargo Air): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

A00142 MST PAINLESS STAINLESS 20NET18

Version 4.0

Revision Date 04/19/2018

Print Date 10/16/2019

Transportation Regulation: IATA (Passenger Air): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

cause birth defects or other reproductive harm. For more

information go to www.P65Warnings.ca.gov.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
xylenes	1330-20-7	100	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards	: Gases under pressure Respiratory or skin sensitisation
SARA 302	: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.
SARA 313	: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
California Prop. 65	
	WARNING: This product can expose you to chemicals including ethylbenzene, benzene, naphthalene, which is/are known to the State of California to cause cancer, and toluene, benzene, which is/are known to the State of California to

Version 4.0

Revision Date 04/19/2018

Print Date 10/16/2019

The components of this product are reported in the following inventories:


DSL	All components of this product are on the Canadian DSL
TSCA	On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION



OSHA - GHS Label Information: Hazard pictograms Warning: Signal word Contains gas under pressure; may explode if heated. May cause an allergic skin Hazard statements reaction. Precautionary statements Prevention: Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves. Pressurized container: Do not pierce or burn, even after use. Response: IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/ attention. Wash contaminated clothing before reuse. Storage: Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50 °C/ 122 °F. Disposal: Dispose of contents/container in accordance with local regulation.

Γ	Version:	4.0
	Revision Date:	04/19/2018

A00142 MST PAINLESS STAINLESS 20NET18

Version 4.0

Revision Date 04/19/2018

Print Date 10/16/2019

Print Date: 10/16/2019

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®,Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®,Rexodan®, Mykal™, and a number of private labeled brands.